

HANDHELD THERMO PRINTER

打印机式温度计

AP-400 Series 系列

NEW MODEL
新产品

Manual Print

手动打印

12:20:05	100.0℃
12:20:19	100.2℃
12:20:30	99.7℃

Interval Print

间隔打印

13.7.25	
AUTO 3S	
12:40:35	25.0℃
12:40:38	27.2℃

Time interval : 3s, 10s, 30s, 1min, 5min, 10min, 30min and 60min

间隔时间 : 3秒·10秒·30秒·1分·5分·10分·30分·60分

Number Print

代码打印

13.7.25	
NUMBER PRINT	
0001	25.0℃
0002	27.2℃
0003	32.3℃

Memory function

记录功能

The memory function makes it possible to batch print the measured data stored in the internal memory. (max.100 lines data)

数据可记录于主机内部后进行统一打印 (最多记录100行)



ANRITSU METER CO.,LTD.



Connector type 连接传感器

2 types of connectors available

有2种插口可供选择

ANP : Miniature size connector

ASP : Standard size connector

AP-450K side view 侧面

AP-400K side view 侧面



Compact and Light weight

小型·轻量

Print function 打印功能

• Manual print 手动打印

Manual print-out is available simply by pushing the **PRINT** key. Measured data with absolute time (Hours: Minutes: Seconds) can be printed.

按 **PRINT** 键可打印测量时间和温度

• Interval print 间隔打印

The **SET** key enables the operator to select a time mode from eight kinds of intervals.

按照设定的间隔打印测量时间和温度

Time interval : 3s, 10s, 30s, 1min, 5min, 10min, 30min and 60min

间隔时间 : 3秒·10秒·30秒·1分·5分·10分·30分·60分

• Number print 代码打印

The numbering print provides the sequential numbering and measured data.

按 **START** 键打印温度数据代码和温度

Memory function 记录功能

The memory function makes it possible to batch print the measured data stored in the internal memory. (max. 100 lines data)

数据可记录于主机内部后进行统一打印 (最多记录100行)

Hold function 固定测量数据

The thermometer stops measurement by the **HOLD** key and holds the present readings.

按 **HOLD** 键, 可固定测量数据并保持该数据的显示

Power supply 电源

4 AA (LR6) alkaline dry cells or AC adaptor (optional accessory)

单3电池 (LR6) 4只或专用AC电源 (另售)

● Specifications

Model	AP-400E AP-450E	AP-400K AP-450K
Input connector	ASP model : AP-400 ANP model : AP-450	
Channel	1ch	
Input (thermocouple type)	type E	type K
Signal source resistance	MAX. 500Ω	
Measurement range	1°C range	-200~800°C
	0.1°C range	-104.9~504.9°C
Measurement accuracy	1°C range	0°C~ : ± (0.1% of reading + 1) °C ~0°C : ± (0.5% of reading + 1) °C
	0.1°C range	0°C~ : ± (0.05% of reading + 0.2) °C ~0°C : ± 0.5°C
Reference junction compensation accuracy	±0.2°C at 25°C ± 10°C	
Temperature coefficient	±0.01% of measurement range / °C : Outside 25°C ± 10°C	
Battery life	Non-printing mode : Approx. 110 hours 1-minute interval : Approx. 120 hours	
Power supply	Dry battery	4 AA Alkaline dry cell batteries
	AC power	AC Adaptor (optional accessories)
Dimensions	approx. 68 (W) × 201 (H) × 42 (D) mm	
Weight	approx. 350g (include batteries)	
Supplied accessories	Soft case, 4 AA Alkaline dry cell batteries, Paper jam fixer, User's manual, Print paper, Test report and User registration form	

● Optional accessories

AC-adaptor
AD-115-500-HR-R (for AC115V)
AD-220-500-HR-R (for AC220V)
Print paper
ACAP4 (5 pcs/set)

ANRITSU ANRITSU METER CO.,LTD.

2-4-5, Shimomeguro,
Meguro-ku, Tokyo 153-0064,
JAPAN

Phone : 81-3-3491-9181

Fax : 81-3-3493-6729

e-mail : sales@anritsu-meter.co.jp

http://www.anritsu-meter.com